EA600 Siren

Compact and effective siren amplifier to meet your needs



FEATURES

- 29 tones available to fit your needs: Common European tones, Wail, Air Horn, Yelp, Two Tone, Martin HI/LO, Whoop, Piercer
- · Compact size, simple to install and use
- Push-to-talk button capability on the PA mic
- · PA volume control on siren amplifier
- Compatible with 8Ω (1x 8Ω or 2x 4Ω) and 11Ω speakers
- · Class D technology with high speed digital switching provides high efficiency, low current draw and great reliability

SPECIFICATIONS

10-30 ∠∠ Vdc		Reverse Polarity Protection $\sqrt{+}$	- 30 +65 C°	ECE R10	
-----------------	--	---	-------------------	------------	--

Input Current Draw	9 amps @ 13.6 Vdc, 4.5 amps @ 27.2 Vdc
Standby Current Draw	<2mA @12.8Vdc, <3.5mA @ 25.6Vdc
Output Watts	100 watts
Siren Frequency Range	350Hz to 2000Hz
PA Audio Frequency Range	300Hz to 10,000Hz
Siren Tones	29 siren tones available
Dimensions	Amplifier: 120mm L x 29mm H x 104mm D PA Mic: 63.5mm L x 94.85mm H x 49.8mm D
Speaker Compatibility	$2x\;4\Omega^*$ 50W Speakers (50EA Speaker) or 1x 11 Ω 100W Speaker (100J or 100U)
Certifications	ECE-R10

*wired in series for 8Ω

PART NUMBERS

ETSAA601

EA600 Siren Only

AVAILABLE ACCESSORIES

PTSAA601

EA600 PA Microphone and Accessory Kit

