

A500 Series Siren

Compact, cost-effective and easy-to-use siren



FEATURES

- Up to 24 tones available: Wail, Yelp, Piercer, HiLo, SUPER HiLo, Alert, Horn and more
- Designed with extra large buttons and appropriate spacing to eliminate incorrect buttons being pushed
- Hands free operating mode available
- Appropriate sound intensity and amplification to provide coverage on the scene
- Built-in protection against over/under voltage, short circuit and reverse polarity
- Available in 100W and 200W versions

SPECIFICATIONS

Input Voltage Range	10-30 Vdc
Amperage Draw	9.5 amps @ 13.6 Vdc (1 x 100W Speaker), 19 amps @ 13.6 Vdc (2 x 100W speakers)
Siren Frequency Range	500Hz to 2000Hz
PA Audio Frequency Range	300Hz to 10,000Hz
Lighting Outputs	3x 8 amp outputs, 6x 0.2 amp outputs
Operating Temperature	-40° C to +65° C (-40° F to +149° F)
Dimensions	<i>Control Unit:</i> 15.2 cm Width x 4.8 cm Height x 18 cm Depth (6" W x 1.89" H x 7.1" D) <i>Controller:</i> 6.35 cm Width x 2.5 cm Height x 12.7 cm Depth (2.5" W x 0.98" H x 5" D)
Mount Types	Holster kit for control panel
Certifications	SAE J1849*, CA Title 13*, ECE R10, CISPR25 Class 2 *with SoundOff 100J, 100U, 100N speakers
Warranty	Three year

CONTACT

Toll free 800.338.7337
Direct 616.896.7100
soundoffsignal.com

PO Box 206
Hudsonville, MI 49426
customerservice@soundoffsignal.com

V0623